

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A refrigeration system (1)-for vapor compression refrigeration cycle including comprising:

a heat source circuit provided with a high temperature compressor; (141) and
a utilization circuit connected to the heat source circuit and provided with an evaporator
(123)-and a low temperature compressor-(131), the refrigeration system (1) comprising:

an operation control means for switchingunit that switches the high temperature
compressor (141)-between an actuated state and a suspended state based on a refrigerant suction
pressure; and

an actuation control means for actuatingunit that actuates the low temperature compressor
(131)-to increase the refrigerant suction pressure of the high temperature compressor (141)-when
the high temperature compressor (141)-is suspended and given conditions, including a condition
concerning a request for cooling in the evaporator, (123)-are met.

2. (Withdrawn) A refrigeration system (2) for vapor compression refrigeration cycle
comprising:

an operation control means for switching a compressor (241) between actuated state and
suspended state based on a refrigerant suction pressure; and

a reference value changing means for reducing a reference value of the refrigerant suction
pressure for judging whether to actuate the compressor (241) or not when the compressor (241)
is suspended and an outside air temperature is reduced from a predetermined temperature.

3. (Withdrawn) The refrigeration system (2) of claim 2, wherein

the reference value changing means is adapted to reduce the reference value in stages based on the amount of reduction in outside air temperature from the predetermined temperature.

4. (Withdrawn) A refrigeration system (3) for vapor compression refrigeration cycle comprising:

an operation control means for switching a compressor (341) between actuated state and suspended state based on a refrigerant suction pressure; and

a power supply control means for supplying open phase current to a motor of the compressor (341) to increase the refrigerant suction pressure increases when the compressor (341) is suspended, an outside air temperature is reduced from a predetermined temperature and a condition concerning a request for cooling in an evaporator (313) is met.